BUILDING RENEWAL™ NEVERFADE®

PRODUCT SPECIFICATIONS: QUICK REFERENCE GUIDE

THE COATINGS SYSTEMS	NEVERFADE® ORIGINAL BASE	NEVERFADE® METAL BASE	BR-W1500 UNIVERSAL PRIMER	BR-W1650 BONDING PRIMER
TYPE	WATER-BASED	WATER-BASED	WATER-BASED	WATER-BASED
MIX	ONE COMPONENT	ONE COMPONENT	ONE COMPONENT	ONE COMPONENT
REDUCTION	MAX 1 - 4 CUPS 8 FL OZ - 38.4 FL OZ	MAX 1 - 4 CUPS 8 FL OZ - 38.4 FL OZ	MAX 2-3 TABLESPOONS, 2 FL OZ - 8 FL OZ	MAX 2-3 TABLESPOONS, 2 FL OZ - 8 FL OZ
VISCOSITY TARGET	63 SECONDS, #3 ZAHN CUP	63 SECONDS, #3 ZAHN CUP	55 SECONDS, #3 ZAHN CUP	54 SECONDS, #3 ZAHN CUP
EQUIPMENT	HVLP, AIRLESS, AIR ASSISTED, BRUSH OR ROLL	HVLP, AIRLESS, AIR ASSISTED, BRUSH OR ROLL	HVLP, AIRLESS, AIR ASSISTED, BRUSH OR ROLL	HVLP, AIRLESS, AIR ASSISTED, BRUSH OR ROLL
FILM THICKNESS	5-6 MILS WET 2 MILS DRY	5-6 MILS WET 2 MILS DRY	3 MILS WET 1 MIL DRY	3 MILS WET 1 MIL DRY
COVERAGE ESTIMATE	250-300 SQ FT/GAL	350-400 SQ FT/GAL	400-450 SQ FT/GAL	400-450 SQ FT/GAL
DRY TO TOUCH	15 MINUTES	15 MINUTES	15 MINUTES	15 MINUTES
RECOMMENDED RECOAT WINDOW	MIN 3 HRS MAX 48 HRS (Same product)	MIN 3 HRS MAX 48 HRS (Same product)	MIN 24 HRS MAX 7 DAYS	MIN 24 HRS MAX 7 DAYS
FULLY CURED	30 DAYS	30 DAYS	7 DAYS	7 DAYS
APPLICATION TEMPERATURE RANGE	55° F – 85° F	55° F – 85° F	55° F – 85° F	55° F – 85° F
HUMIDITY	5° F ABOVE DEW POINT	5° F ABOVE DEW POINT	5° F ABOVE DEW POINT	5° F ABOVE DEW POINT
ADHESION TO SUBSTRATES	PRIMER REQUIRED ADHESION: ASTM D3359	PRIMER REQUIRED ADHESION: ASTM D3359	STUCCO, EIFS, VINYL, MASONRY, CONCRETE, FIBER CEMENT, WOOD ADHESION: ASTM D3359	PLASTICS, FERROUS & NON-FERROUS METALS, COATED SURFACES INCLUDING: SILICONIZED POLYESTER, KYNAR 500®, FEVE COATINGS, AND POWDER COATINGS ADHESION: ASTM D3359

For technical assistance contact **ppcprotectivecoatings@pittsburghpaints.com**

The Pittsburgh Paints Co.
Cranberry Twp, PA 16066
PIttsburghPaints.com

© 2026 The Pittsburgh Paints Co. All Rights Reserved. *Building Renewal* and the *P Logo & Pittsburgh Paints* are trademarks of The Pittsburgh Paints Co. *Kynar* and *Kynar Aquatec* are registered trademarks of Arkema Inc. *NeverFade* is a registered trademark of Akron Paint & Varnish, Inc., dba APV Engineered Coatings. PL_2010358

PITTSBURGH PAINTS
PROTECTIVE COATINGS